

The RH800 provides driving behaviour data via an on-board accelerometer which allows for a camera to be activated on harsh manoeuvres. This also means that the unit can provide FNOL notifications and triggered video in the event of a RTA.

Integrating HD camera functionality with our market leading telematics means that users can benefit from a wealth of features, including driving behaviour scoring, vehicle health alerts, driver ID support, remote tachograph downloads, livestreaming and in-cab driver feedback via our accessory range.

Trakm8's RH800 connected camera solution provides up to 4 channels of HD video and image uploads. We also have an extensive range of camera lenses and accessories that allows for bespoke camera fitment requirements. This is the perfect solution to help your fleet become DVS compliant.

Features

- HD video resolution
- 4 channel capability for bespoke recording requirements
- Vehicle health data provided via Trakm8's Connectedcare solution
- Vehicle diagnostics
- Integrated telematics
- GPS tracking
- G-force sensor
- Compliant remote tachograph download (ACC540)
- Video on demand
- Automatic upload and transmission of harsh manoeuvres and collisions
- Improve driver performance using event based video coaching
- Live video streaming (4G)
- Secure encrypted firmware (tamper proof)
- Secure video transfer
- Automatically capture and report on crash FNOL events
- Full API data-push functionality with 3rd parties to help improve claims efficiency
- Geofencing
- Insight reporting
- Choose from our comprehensive reports library or create your own bespoke reports and dashboards
- Monitor KPIs that matter to your business
- Create bespoke camera upload rules via our trigger service for an autonomous solution
- \blacksquare In-cab driver feedback (with optional audio alerts) via ACC750
- Driver ID via RFID card (ACC750) / Tacho Head (ACC530)
- Installation options: Hardwired by approved installer
- Inputs: 1x Power Take Off (PTO), 4x general inputs for monitoring (indicators, reversing, doors etc)
- Built in Output for use as an immobiliser
- Driver button for event alerting / image capture

Camera & Monitor Accessories Options

In-cab



R20235 In-cab monitor



R20400 Road & driver facing



R20401 Road facing (Separate)



R20402 Driver facing (Separate)

Internal Camera Options - IP65



R20410 Internal wide-angle



R20411 Internal dome

External Camera Options - IP67



R20423 External dome



R20420/R20202 Side facing left/right



R20421/R20201 Rear facing



R20422 Mini side facing left/right



RH800

Product Information Sheet

Specifications

Supply Voltage & Current Draw

Supply Voltage

- 6V 30V (12V/24V Vehicles)
- Super Cap (power retention)

Current Draw

- 6mA @12V Sleep mode
- 1.8A peak @12V

Connectivity

- Bluetooth Low Energy (BLE 4.2)
- GPS location technology
- External antennas
- 4G communications
- Vehicle CAN 1 interface
- Tacho CAN 2 interface

Weight

480grams

Dimensions

LxWxH:

■ 190 x 122 x 33 mm

Enclosure

Black anodised aluminium

Operating Temperature

-20°C to +85°C

Certification

CE, UKCA and E-Mark

Mounting

 Secured to vehicle chassis using fitments on the enclosure

Inputs

- 1x Power Take Off (PTO)
- 4x general inputs for monitoring (indicators, reversing, doors etc)

Outputs

- 1x High sided drive
- Can be configured to drive automotive relay (Immobilisation)

Accessories

Bluetooth Business/Private & Alert Button - ACC700

- Business/Private journey switching
- Driver Alert
- DriverID via Tacho Head (Wired)

Bluetooth DriverID & Alert Button

- ACC710
- Business/Private journey switching
- Driver Alert
- DriverID via Dallas Key

Bluetooth DriverID & Driver Feedback

- ACC750

- Clear auto-dimming display
- Real-time driver score updates and alerts poor driving technique
- Driver identification using all standard door entry and employee identity card solutions and NFC from a mobile phone
- Multi-functional button:
 - a. Business or Private journey selection
- b. Driver Alert

Tacho DriverID - ACC530

- Driver identification via Tachograph Card
- Driver working states

Tacho Data Download - ACC540

- All the above Driver ID features
- Over air data download
- Vehicle files
- Driver files
- Compliant with third party processing

Driver Button (CAB602) - Included In Bundle

- Business / Private Journey
- Alert button

CAN Connect Interface (ACC558) - Included In Bundle

- OBDII interface Connectedcare
- None invasive connection

RH8-512GB

Bundles

4 Channel connected Camera with 512Gb memory

RH8-1TB

4 Channel connected Camera with 1Tb memory

RH8-2TB

4 Channel connected Camera with 2Tb memory

Cables / Antennas

CAB942 - Included In Bundle

• 4 way Main power and Ignition Cable

CAB943 - Included In Bundle

■ 16 way I/O connector

ANT141 - Included In Bundle

GPRS/GPS Combo antenna
(Fakra Codes D-Violet, K-Yellow, C-Blue)

ANT142 - Included In Bundle

• BLE Bluetooth Antenna

R20215

■ 5m Camera / monitor extension cable

R20216

■ 7.5m Camera / monitor extension cable

R20217

• 10m Camera / monitor extension cable

R20218

■ 15m Camera / monitor extension cable

R20219

20m Camera / monitor extension cable

Camera's / Monitor

R20235

In-cab monitor 7" with speaker

R20400

Road & driver facing

R20401

Road facing

R20402

Driver facing

R20410

Internal wide-angle

R20411

Internal dome

R20421/R20201

Rear facing

R20420/R20202

Side facing left/right

R20422

Mini side facing left/right

R20423

External dome

R20423B

Surface mount bracket for R20423

Speakers

R20302

Reverse Speaker, 97dB - 12W-24W

D2030/

Left Turn Speaker - 12W-24W

Email: info@trakm8.com Call: +44 (0) 330 311 5157 Web: www.trakm8.com

